TYPICAL FORMULA

Active ingredient(s)	50,00 g/l	to	800,00 g/l
Anti-freeze agent	30,00 g/l	to	100,00 g/l
Surfactant(s)*	20,00 g/l	to	60,00 g/l
Thickening agent(s)	1,00 g/l	to	10,00 g/l
Biocide	0,50 g/l	to	1,00 g/l
Antifoam agent	0,50 g/l	to	5,00 g/l
Water	Quantity adjusted to 1 l		

^{*} Wetting-Dispersing agent(s).

DEVELOPMENT STEPS

- 1 Check the active ingredient (a.i.) properties.
 - · Solid powder
 - Insolubility of the a.i. in water (ideally solubility < 100 ppm)
 - High melting point of the a.i. (ideally > 80°C)
 - A.i. non sensitive to hydrolysis.
- 2 Identify the right wetting-dispersing agent(s).

Range of Tensiofix® wetting-dispersing agents

Our alkylphenol free range of wetting-dispersing agents consists in 4 main products:

Tensiofix® 96 DB 08

- Tensiofix® SC
- Tensiofix® CGA 213
- Tensiofix® XA 265

User guidelines

As first trial, we recommend testing Tensiofix® 96 DB 08 at 3% w/w.

Tensiofix® 96 DB 08 gives good results with a lot of a.i.

In case of crystal growth or viscosity increase, the combination of Tensiofix® 96 DB 08 with another wetting-dispersing agent, still with a total of 3% w/w of surfactants is recommended.

Tensiofix® 96 DB 08

+

Tensiofix® XA 265 Tensiofix® CGA 213 Tensiofix® SC

2,5 % w/w

0,5 % w/w

3

Identify the other components:

Anti-freeze agent:

- MEG, DEG, propylene glycol...
- 3% is a minimum for stability; 10% enables a good stability up to -10°C.

Thickening agent

The main families of thickening agents used in our laboratory are natural gums (Tensiofix® 821) and mineral clays.

Antifoam

We use mainly organic antifoam (Tensiofix® LO 51).

MATERIAL REQUIRED

- · Premix preparation: high shear homogeniser
- Wet grinding: glass beads grinder
- Final homogenisation: simple propeller.







S.A. Ajinomoto OmniChem N.V. Rue Emile Francqui, 7 B-1435 Mont-Saint-Guibert - Belgium Tel. +32 (0) 10 48 31 11 www.tensiofix.com



