

Tensiofix® HSN

TECHNICAL DATA SHEET

Version : V2023/01 - effective 2023 07 01

Composition

- Nonionic surfactants approx. 99%
- Water max. 0,5%

Appearance at 20°C

Cloudy yellow liquid

Specific gravity

- at 40°C approx. 0,94

Melting range

19 to 31°C

pH

5 - 7

Viscosity in mPa.s (Contraves, DIN 125-50 rpm)

- at 40°C approx. 3

Solubility at 20°C

Soluble in water, aromatic hydrocarbons, alcohols, ketones

Flash point (PMCC)

> 100°C

Principal use

Emulsifier

Standard packaging

200 kg net drum

US EPA classification

Exempt from tolerance under EPA regulation 40CFR, 180.930

Storage & Handling

A Safety Data Sheet is available upon request.

Tensiofix® HSN must be used as clear liquid and homogenised.

If unclear, it must be heated above its melting point until obtaining a clear liquid + homogenised.



S.A. Ajinomoto OmniChem N.V.
Rue Emile Francqui, 7
B-1435 Mont-Saint-Guibert - Belgium
Tel. +32 (0) 10 48 31 11
Tensiofix_tech_service@omnicem.be



The information in this document is, to our best knowledge, correct and accurate, but all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Ajinomoto OmniChem disclaims any liability incurred in connection with the use of these data or suggestions. Furthermore, nothing contained herein shall be construed as a specification or recommendation to use any product in conflict with existing patents covering any material or its use. Tensiofix® is a registered trademark of Ajinomoto OmniChem.