

# Tensiofix® ISR 1120

## TECHNICAL DATA SHEET

Version : V2023/01 - effective 2023 07 01

### Composition

- Red pigment ..... 35-45%
- Inerts ..... 60-40%

### Appearance at 20°C

Red liquid

### Specific gravity

- at 20°C ..... approx. 1,08

### Melting range

pH ..... 7 - 10

### Viscosity in mPa.s (Contraves, DIN 125-50 rpm)

- at 50°C ..... To be determined

### Solubility at 20°C

Dispersible in water

Flash point (PMCC) ..... > 100°C

### Principal use

Pigment formulation

### Standard packaging

200 kg net drum

### Storage & Handling

A Safety Data Sheet is available upon request.  
Tensiofix® ISR 1120 must be homogenised before use.



S.A. Ajinomoto OmniChem N.V.  
Rue Emile Francqui, 7  
B-1435 Mont-Saint-Guibert - Belgium  
Tel. +32 (0) 10 48 31 11  
Tensiofix\_tech\_service@omnicem.be



The information in this document is, to our best knowledge, correct and accurate, but all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Ajinomoto OmniChem disclaims any liability incurred in connection with the use of these data or suggestions. Furthermore, nothing contained herein shall be construed as a specification or recommendation to use any product in conflict with existing patents covering any material or its use. Tensiofix® is a registered trademark of Ajinomoto OmniChem.