

Tensiofix® KL 70

TECHNICAL DATA SHEET

Version : V2023/01 - effective 2023 07 01

Composition

- Anionic surfactants approx. 70%
- Solvent approx. 30%
- Water max. 0,5%

Appearance at 20°C

Yellow to light brown viscous liquid

Specific gravity

- at 50°C approx. 0,98

Melting range

< -10°C

pH

5 - 7

Viscosity in mPa.s (Contraves, DIN 125-50 rpm)

- at 50°C approx. 800

Solubility at 20°C

Soluble in aromatic hydrocarbons, alcohols, ketones. Not soluble in water

Flash point (PMCC)

34°C

Principal use

Emulsifier

Standard packaging

200 kg net drum

US EPA classification

Exempt from tolerance under EPA regulation 40CFR, 180 910 and 930

Storage & Handling

Product is ADR classified.

A Safety Data Sheet is available upon request.

Tensiofix® KL 70 must be used as clear liquid and homogenised.

If unclear, it must be heated above its melting point until obtaining a clear liquid + homogenised.



S.A. Ajinomoto OmniChem N.V.
Rue Emile Francqui, 7
B-1435 Mont-Saint-Guibert - Belgium
Tel. +32 (0) 10 48 31 11
Tensiofix_tech_service@omnicchem.be



The information in this document is, to our best knowledge, correct and accurate, but all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Ajinomoto OmniChem disclaims any liability incurred in connection with the use of these data or suggestions. Furthermore, nothing contained herein shall be construed as a specification or recommendation to use any product in conflict with existing patents covering any material or its use. Tensiofix® is a registered trademark of Ajinomoto OmniChem.