

# Tensiofix<sup>®</sup> NTM

## TECHNICAL DATA SHEET

Version : V2023/01 - effective 2023 07 01

### Composition

- Nonionic surfactants ..... approx. 99%
- Water ..... max. 0,5%

### Appearance at 20°C

Cloudy yellow liquid

### Specific gravity

- at 50°C ..... approx. 0,98

### Melting range

22 to 31°C

### pH

5 - 7

### Viscosity in mPa.s (Contraves, DIN 125-50 rpm)

- at 50°C ..... approx. 100

### Solubility at 20°C

Soluble in water, aromatic hydrocarbons, alcohols, ketones

### Flash point (PMCC)

> 100°C

### Principal use

Dispersing agent, emulsifier

### Standard packaging

200 kg net drum

### US EPA classification

Exempt from tolerance under EPA regulation 40CFR, 180.910-930-940-960

### Storage & Handling

Product is ADR classified.

A Safety Data Sheet is available upon request.

Tensiofix<sup>®</sup> NTM must be used as clear liquid and homogenised.

If unclear, it must be heated above its melting point until obtaining a clear liquid + homogenised.



S.A. Ajinomoto OmniChem N.V.  
Rue Emile Francqui, 7  
B-1435 Mont-Saint-Guibert - Belgium  
Tel. +32 (0) 10 48 31 11  
Tensiofix\_tech\_service@omnicchem.be

