

Tensiofix® XA 265

TECHNICAL DATA SHEET

Version : V2023/01 - effective 2023 07 01

Composition

- Blend of anionic and nonionic surfactants approx. 99%
- Phosphoric acid max. 2%
- Water max. 0,5%

Appearance at 20°C

Yellow hazy viscous liquid

Specific gravity

- at 30°C approx. 1,04

Melting range

18 to 22°C

pH

1,5 - 3

Viscosity in mPa.s (Contraves, DIN 125-50 rpm)

- at 30°C approx. 600

Solubility at 20°C

Soluble in water, aromatic hydrocarbons, alcohols, ketones

Flash point (PMCC)

> 100°C

Principal use

Emulsifier, dispersing agent, wetting agent

Standard packaging

200 kg net drum

US EPA classification

Exempt from tolerance under EPA regulation 40CFR, 180.920

Storage & Handling

A Safety Data Sheet is available upon request.

Tensiofix® XA 265 must be used as clear liquid and homogenised.

If unclear, it must be heated above its melting point until obtaining a clear liquid + homogenised.



S.A. Ajinomoto OmniChem N.V.
Rue Emile Francqui, 7
B-1435 Mont-Saint-Guibert - Belgium
Tel. +32 (0) 10 48 31 11
Tensiofix_tech_service@omnicchem.be

The logo for Tensiofix, featuring the word 'TENSIOFIX' in a bold, blue, sans-serif font with a registered trademark symbol. Below the text is a thick orange horizontal bar.

The information in this document is, to our best knowledge, correct and accurate, but all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Ajinomoto OmniChem disclaims any liability incurred in connection with the use of these data or suggestions. Furthermore, nothing contained herein shall be construed as a specification or recommendation to use any product in conflict with existing patents covering any material or its use. Tensiofix® is a registered trademark of Ajinomoto OmniChem.